



SWC's VisView™ offers a more efficient way to handle inmate visits by reducing time spent escorting inmates, provides a safer environment for facility staff and reduces introduction of contraband into facility.

Complete IP Based Solution

- Fully scalable
- Policy driven
- Fully automated
- Conflict checking eliminates manual process of checking JMS, notes, logs etc.

Advanced Scheduling Features

- On-demand connections
- Officer Scheduling
- Public Web-Based Scheduling
- Lobby Kiosk Scheduling

Audio/Video Recording

- Utilizes standard off-the-shelf servers
- Each session stored as a single file (audio & video)
- Cost effective & scalable

Reporting

- Full audit trail for entries, edits or cancellations
- By visitor, inmate, housing unit
- Hardcopy or electronic (PDF, XLS or HTML)

**SWC is a Complete Turnkey Solution
for your Video Visitation Needs**



Video:

Video Standards - H.264, H.323
Rate: 64Kbps - 2Mbps
Video Resolution - CIF (352 x 288 pixels), SIF (352 x 240 pixels), QCIF (176 x 144 pixels)
Video Frame Rates - Up to 15 fps: 64 - 320 Kbps,
Up to 30 fps: 384 Kbps

Audio:

Audio Standards - G.711, G.722, G.723.1,
G.728, G.729
Full duplex

Monitor:

17" LCD, standard VESA mounting
Resolution up to 1280 X 1024
Contrast Ratio - 800:1
Brightness - 250cdm²
Response Time - 5ms
Viewing Angle - 160°/ 160°
Color Support - 16.7 million colors

Camera:

Imaging Device - 1/3-inch interline transfer CCD
2:1 interlace
Active Picture Elements - NTSC: 768 (H) x 494 (V)
Scanning System - NTSC: 525 lines, 60 fields/sec
Horizontal Resolution - 520 TV lines
Auto White Balance - 2500° to 7200°K
3-9 MM Vari-focal lens

Handset:

Electret Transmitter
4' armored cable with internal lanyard
Vandal Resistant

Booth Enclosure:

12 Gauge C.R.S.
Powder coated for durability
Removable front cover
Easily replaceable 3/8" polycarbonate window
Venting for equipment longevity

Electrical:

120 VAC or 12 VDC operation

